

LUX METER (LIGHT INTENSITY METER)

AGRONIC - Lx101 ₹ 2000/-



RANGE: 0 to 50000 Lux in 3 ranges of 0 to 2000, 0 to 20000 and 0 to 50000 Lux. Range selection is provided with front panel control.

ACCURACY: ± 5% ± 2 least counts.

RESOLUTION:

1 in the range of 0 to 2000 Lux.
10 in the range of 0 to 20000 Lux.
100 in the range of 0 to 50000 Lux.

DATA HOLD : Data hold facility is provided.

DISPLAY: 3 ½ digit, 7 segment LCD type of 12.5mm height. X10, X100, data hold and low battery indications are provided.

SENSOR: Separately attached light sensor allows user to take measurements at an optimum position.

POWER REQUIREMENTS:

9 volts battery.

SIZE & WEIGHT:

23 mm (H) x 73 mm (W) x 1408 mm(L). 160gms.

STANDARD ACCESSORIES: Battery, Instruction manual and carrying cover.

TEMPERATURE CUM HUMIDITY METER

(HYGRO- THERMOMETER-CLOCK)

AGRONIC - TH ₹ 1500/-



AGRONIC-TH measures minimum, maximum and real time values of room temperature and humidity.

AGRONIC-TH also displays time in hours and minutes in 12 and 24 hours formats.

Facility of daily alarm, alarm off and memory daily reset on/off are provided.

RANGE, RESOLUTION AND ACCURACY: 0 to +50°C with resolution of 0.1°C and accuracy of ±1°C.

+32 to +120°F with resolution of 0.1°F and accuracy of ± 1.8°F.

°F or °C selection with the function selection switch.

10 to 90% relative humidity with resolution of 1% and accuracy of ±5% from 40% to 80% (±8% for remaining range).

0 to 12 or 0 to 24 hours with resolution of 1 minute and accuracy of 3 seconds per day.

ALARM: Alarm duration is 12 minutes.

TEMPERATURE DISPLAY: 3 ½ digit, 7 segment, LCD type of 20mm height. Decimal point, %, °F and °C displays are provided.

HUMIDITY DISPLAY: 2 digit, 7 segment LCD type of 20mm height.

Comfort, wet, dries and % displays are provided.

COMFORT appears when temperature is from 20°C to 26°C (68°F to 78.8°F) and relative humidity is from 50% to 70%.

WET appears for any temperatures when relative humidity is higher than 70%.

DRY appears for any temperatures when relative humidity is below 50%.

TIME DISPLAY: 4 digit.7 segment LCD type of 20mm height. AM, PM and alarm displays are provided.

All of the displays are updated every 10 seconds.

POWER REQUIREMENTS: 1.5 volts, size AAA cell.

SIZE AND WEIGHT: 110 mm (H) x 98 mm (W) x 21 mm (D). 130gms.

Foldaway stand help place unit on table at convenient viewing angle. Wall mounting key hole helps in mounting the unit on wall.

STANDARD ACCESSORIES: 1.5 volts, cell and instruction manual.

Manufactured / Marketed by
AGRAWAL ELECTRONICS

201, Shivshakti Indl. Estate, Opp. Damodar Park, Near Shreyas Talkies, L.B.S . Marg, Ghatkopar(W), Mumbai 400086, India.
Tel : 022 2500 0231, Fax : 022 2500 1251, E-mail : agronic@agronic.net, Website : www.agronic.net

We reserve our right to revise the above data without prior intimation. The rates above are for supplies within India.
VAT extra at 12.5% (2% against C form for outside Maharashtra customers). Freight at actuals extra. The rates are valid until 30.06.2011